



MICROMEGA

PW250

## The PW-250 Stereo Power Amplifier

The PW-250 is the first of two stereo power amplifiers which are compact in size and in association with the PA-20 can fully satisfy the demands of all modern speakers. Together they are capable of providing effortless reproduction and respect all details of the musical message.

Thanks to its class D amplification modules, the PW-250 is dynamic and combines transparency with a real sense of efficiency.

### Technical characteristics

Power per channel/4 $\Omega$	250 W
THD at Pmax / 2 (20 Hz – 20 kHz)	< 0.05%
Output noise (20 Hz-20 kHz)	30 $\mu$ V
Input impedance	100 k $\Omega$
Output impedance (1 kHz)	< 20 m $\Omega$
Frequency response (-3 dB)	10 Hz-50 kHz
Voltage gain	26 dB
Efficiency at Pmax	92%
Idle losses	8 W
STBY current	10 mA
Current limit	20 A
Power consumption	600 W
Dimensions (W x D x H mm)	430 x 300 x 70 mm
Weight	12.0 kg

**AUDIS SARL**, 13-15 rue du 8 mai 1945 - 94470 Boissy Saint Léger - FRANCE

Tel: 01 43 82 88 60 Fax: 01 43 82 61 29 E-mail: [info@micromega-hifi.com](mailto:info@micromega-hifi.com) Internet: [www.micromega-hifi.com](http://www.micromega-hifi.com)

Audis SARL has the right to modify the technical and performance characteristics of its audio-video products without prior notification.